

UNIFIT - Universal Fittings



Description:

The Universal **Plas-fit** connector is especially designed for the water transportation industry. The Unifit connector line connects simply and reliably between polyethylene pipes and pipes made from various other materials: copper, galvanized iron, PVC and more.

Technical specifications:

- The connector has a particularly flexible mechanism allowing connections to diameters in the 15-53 mm range
- Double sealing - hydraulic and mechanical
- Available as a complete unit or as a kit for integration with a variety of Plas-fit connectors
- Can be disassembled and reassembled
- Working pressure: PN 16



Carton Box size - in the contents page.

UNIFIT COUPLING



Size	Cat. No.	
3/8"-1/2"	150 15 M 50 16	16mm
3/8"-1/2"	150 15 M 50 20	20mm
3/8"-1/2"	150 15 M 50 25	25mm
1/2"-3/4"	150 21 M 50 20	20mm
1/2"-3/4"	150 21 M 50 25	25mm
1/2"-3/4"	150 21 M 50 32	32mm
3/4"-1"	150 27 M 50 25	25mm
3/4"-1"	150 27 M 50 32	32mm
3/4"-1"	150 27 M 50 40	40mm

UNIFIT ELBOW



Size	Cat. No.	
3/8"-1/2"	150 15 Z 50 20	20mm
3/8"-1/2"	150 15 Z 50 25	25mm
1/2"-3/4"	150 21 Z 50 25	25mm
1/2"-3/4"	150 21 Z 50 32	32mm
3/4"-1"	150 27 Z 50 40	40mm

UNIFIT CONVERSION KIT



Size	Cat. No.	
15 - 21"	150 15 E 58 00	25mm
21 - 27"	150 21 E 58 00	32mm