

Divisible Microduct Repair Coupling

Product Technical sheet



ABOUT

Plas-Fit Divisible Microduct Connector provides high quality, effective and simple solution to gas and watertight duct sealing requirements.

This modular system can be fitted easily onto new and existing installations.

Thanks to its small and compact design, it can be installed in most situations even in hard to reach places.

Sealing rating : Up to 15 Bar (220 PSI)

The Divisible Connector consists of two halves which should be fitted around the connection area. The connector is then sealed by sliding on the side clasps.

Very simple with no tools required. The assembly is supplied with all components in place.

FEATURES

- Fast & easy assembly
- Tool free installation
- Can be used for direct burial installations
- Retrofittable, can be installed any time, any place
- Slide-on clasps
- Ergonomic design
- Gas and watertight up to 15 bar for 30 minutes

AVAILABLE PRODUCTS

size	Cat No
7mm	40007RC0007
10mm	40010RC0010
12mm	40012RC0012
14mm	40014RC0014
16mm	40016RC0016
18mm	40018RC0018
20mm	40020RC0020



Divisible Microduct Repair Coupling



DIMENSIONS

Duct Size O.D. [mm]	Nominal OD [mm]	Length [mm]
7	26.2	80
10	29.25	80
12	31.25	80
14	33.25	100
16	35.25	100
18	37.4	100
20	39.2	100

